

# FRAME SPECS

<b>Frame</b>	2016 Advocate Hayduke
<b>Wheel Size</b>	27.5x3 or 29x2.3
<b>Fork</b>	Designed for 120mm travel suspension fork with 51mm offset, or rigid forks with at least 490mm A-C
<b>Headset</b>	ZS44/28.6 upper and EC44/40 lower. Use EC44 cup with reducer plate for 1 1/8" straight steerers
<b>Seatpost</b>	31.6mm with internal routing for Stealth Dropper seatposts
<b>Seat Collar</b>	34.9mm Thompson Elite seat collar included
<b>Front Derailleur</b>	Top pull routing for direct-mount style, adapter clamp recommended
<b>Bottom Bracket</b>	BB92 Pressfit standard, 41mm ID smooth bore, 92mm wide
<b>Crank Compatibility</b>	Compatible with all BDDST 54mm chainline cranks in 1x and 2x drivetrains, with a max tooth count of 34t and 51mm chainline in 1x only
<b>Rear Brake</b>	51mm I.S for 160mm rotor. 160mm rotor requires +0 adapter
<b>Axle Spacing</b>	Completely modular rear dropout system to allow geared and singlespeed setups in 148mm axle spacing. SRAM 178m Maxle Ultimate is used and included with any of these setups
<b>Tire Clearance</b>	Designed for 27.5x3" tire. Actual frame measurements are 88mm inside frame clearance for 27.5" and 72mm for 29"
<b>Water Bottle Mounts</b>	1 per frame on small & 2 per frame on all other sizes
<b>Cable Routing</b>	Full housing, including Stealth Dropper seatpost routing
<b>Color</b>	Hayduke Jeep Blue or White

# FRAME SPECS

<b>Frame</b>	2016 Advocate Watchman
<b>Wheel Size</b>	26x4"
<b>Fork</b>	Designed for 100mm travel suspension fork with 51mm offset (Rockshox Bluto) or rigid forks with 485mm axle to crown length
<b>Headset</b>	ZS44/28.6 Upper and EC44/40 lower. Use EC44 Cup with reducer plate for 1 1/8" straight steerers
<b>Seatpost</b>	31.6mm with internal routing for Stealth Dropper seatposts
<b>Seat Collar</b>	34.9mm. Thomson Elite seat collar included
<b>Front Derailleur</b>	Top pull routing for direct-mount style, adapter clamp recommended
<b>Bottom Bracket</b>	SRAM PF121 Pressfit standard, 41mm ID smooth bore, 121mm wide
<b>Crank Compatibility</b>	Compatible with all 65mm chainline cranks in 1x and 2x drivetrains, with a max tooth count of 34t
<b>Rear Brake</b>	51mm I.S for 160mm rotor. 160mm rotor requires +0 adapter
<b>Axle Spacing</b>	Completely modular rear dropout system to allow geared and singlespeed setups in 177mm axle spacing. SRAM 205mm Maxle Ultimate is used and included with any of these setups
<b>Tire Clearance</b>	Designed for 26x4" tire. Actual frame measurements are 126mm inside frame clearance, may clear some 4.8" tires with drivetrain modifications
<b>Water Bottle Mounts</b>	2 per frame on Small & 3 per frame on all other sizes
<b>Cable Routing</b>	Full housing, including Stealth Dropper seatpost routing
<b>Color</b>	Turquoise or Gray

# FRAME SPECS

<b>Frame</b>	2016 Advocate Lorax
<b>Wheel Size</b>	700cx38c
<b>Fork</b>	Advocate Lorax full-carbon tapered cross fork, post-mount disc break for 160mm rotor
<b>Headset</b>	ZS44/28.6 upper and EC44/40 lower. Use EC44 Cup with reducer plate for 1 1/8" straight steerers
<b>Seatpost</b>	27.2mm
<b>Seat Collar</b>	30.0mm
<b>Front Derailleur</b>	28.6mm band-clamp style, bottom pull
<b>Bottom Bracket</b>	Shimano BB86 standard, 41mm smooth bore, 86mm wide standard
<b>Crank Compatibility</b>	Compatible with all compact double road cranks
<b>Rear Brake</b>	51mm I.S for 160mm rotor. 160mm rotor requires +0 adapter
<b>Axle Spacing</b>	Completely modular rear dropout system to allow geared and singlespeed setups in 135mm axle spacing. Comes with 135mm QR plates for derailleur
<b>Tire Clearance</b>	Designed for a 700cx40c tire including fenders, or up to 45c without
<b>Water Bottle Mounts</b>	3 per frame on all sizes
<b>Cable Routing</b>	Full housing for brake, downtube shifter mounts / cable stops for derailleurs
<b>Color</b>	Midsummer in Minnesota Green