

FRAME SPECS

Frame	2016 Advocate Watchman
Wheel Size	26x4"
Fork	Designed for 100mm travel suspension fork with 51mm offset (Rockshox Bluto) or rigid forks with 485mm axle to crown length
Headset	ZS44/28.6 Upper and EC44/40 lower. Use EC44 Cup with reducer plate for 1 1/8" straight steerers
Seatpost	31.6mm with internal routing for Stealth Dropper seatposts
Seat Collar	34.9mm. Thomson Elite seat collar included
Front Derailleur	Top pull routing for direct-mount style, adapter clamp recommended
Bottom Bracket	SRAM PF121 Pressfit standard, 41mm ID smooth bore, 121mm wide
Crank Compatibility	Compatible with all 65mm chainline cranks in 1x and 2x drivetrains, with a max tooth count of 34t
Rear Brake	51mm I.S for 160mm rotor. 160mm rotor requires +0 adapter
Axle Spacing	Completely modular rear dropout system to allow geared and singlespeed setups in 177mm axle spacing. SRAM 205mm Maxle Ultimate is used and included with any of these setups
Tire Clearance	Designed for 26x4" tire. Actual frame measurements are 126mm inside frame clearance, may clear some 4.8" tires with drivetrain modifications
Water Bottle Mounts	2 per frame on Small & 3 per frame on all other sizes
Cable Routing	Full housing, including Stealth Dropper seatpost routing
Color	Turquoise or Gray