

FRAME SPECS

Frame	2016 Advocate Hayduke Titan
Wheel Size	27.5x3 or 29x2.3
Fork	Designed for 120mm travel suspension fork with 51mm offset, or rigid forks with at least 490mm A-C
Headset	ZS44/28.6 upper and EC44/40 lower. Use EC44 cup with reducer plate for 1 1/8" straight steerers
Seatpost	31.6mm with internal routing for Stealth Dropper seatposts
Seat Collar	34.9mm Thompson Elite seat collar included
Front Derailleur	Top pull routing for direct-mount style, adapter clamp recommended
Bottom Bracket	BB92 Pressfit standard, 41mm ID smooth bore, 92mm wide
Crank Compatibility	Compatible with all BODST 54mm chainline cranks in 1x and 2x drivetrains, with a max tooth count of 32t and 51mm chainline in 1x only
Rear Brake	51mm I.S for 160mm rotor. 160mm rotor requires +0 adapter
Axle Spacing	Completely modular rear dropout system to allow geared and singlespeed setups in 148mm axle spacing. SRAM 174m Maxle Ultimate is used and included with any of these setups
Tire Clearance	Designed for 27.5x3" tire. Actual frame measurements are 88mm inside frame clearance for 27.5" and 72mm for 29"
Water Bottle Mounts	1 per frame on small & 2 per frame on all other sizes
Cable Routing	Full housing, including Stealth Dropper seatpost routing
Color	Brushed Titanium with choice of decal accent color